

## NMSub® Loudspeaker

---



The NM SUB loudspeaker expresses the maximum SPL capability with remarkable low frequency extension in so reduced a size.

It is the result of an extensive search on components and careful mechanical design, in order to create a fully integrated, modular, eclectic and flexible bass system.

The NM MM subwoofer series is composed by 2 models, both with identical technology and SPL but different bass extensions, each of them available in marine natural or coated wood.

All these speakers can be driven by Powersoft® "Ottocanali DSP", "X" or "K" series amplifiers, with dedicated presets

### Specifications

### NMSub

Frequency response $\pm 3$ db	45 ÷ 150 Hz
Efficiency (1W/mt)	98 db
Program power	4.000 W (2.000W)
SPL max (1 mt)	134 db (131db)
Impedance	4 $\Omega$
Coverage	360° (it depends on array configuration)
Drivers	2 x 12" Woofer, very long excursion, 4" voice coil
Connections	2 x SpeakON® 4 wires
Dimensions (cm)	70L x 43H x 35P
Weight (Kg)	26

Sonus Audio Services srl reserves the right to make modifications without prior notice.

NM SUB is a medium throw subwoofer loudspeaker in a VLLA series.

Thanks to their reduced dimensions, the cabinets can be installed in any configuration, even coupling them in length, which has no virtual limits, to create an effective sub-line-source.

A 2.000W+2.000W/4 Ohm (at least) power (stereo) amplifier will easily drive 2 x NM SUB. It is necessary to use exclusively 4 poles cables, with SpeakON® connector, since the system works with cross connection between 2 loudspeakers (a single 4 wires cable connects 2 subs).

On a Powersoft® "Ottocanali DSP", "X" or "K" platform presets for all the loudspeakers are available. Each NM-SUB subwoofer, is able to match with two MICRO 3.8.16 maintaining the same SPL capacity.

